

**OLD WORLD
STONE VENEER™**

THE BEAUTY OF NATURE, PRESERVED IN STONE.

www.oldworldstoneveneer.com

Castle

Castle features large format square and rectangular pieces. It is typically installed with a mortar joint, but it may be installed in a dry-stacked style with additional cutting and fitting.



▲ **Cortland**

Heights: 4" to 15"
Lengths: 5" to 15.5"



▲ **Deep River**

Heights: 5" to 13"
Lengths: 8" to 25"



▲ **Hudson Gorge**

Heights: 3" to 14"
Lengths: 6" to 16.5"



▲ **Manchester**

Heights: 4" to 16"
Lengths: 6" to 16"



▲ **Newport**

Heights: 3" to 15"
Lengths: 6.5" to 19"



■ **Plymouth**

Heights: 6" to 12.5"
Lengths: 8" to 21.5"



▲ **Sheridan**

Heights: 4" to 10"
Lengths: 8" to 25"



Castle Deep River

Dressed Ashlar

Dressed Ashlar features rectangular pieces with clean lines and smooth edges. Its rough textured surface creates a natural, weathered appearance. It has a mix of pre-selected sizes, allowing for easier installation with minimal cutting. It is often installed in a dry-stacked style, but it can be installed with a mortar joint.



 **Everest**

Heights: 2", 3", 4", 6"
Lengths: 4" to 16"



 **Lafayette**

Heights: 2", 3", 4", 6"
Lengths: 4" to 16"

Homestead Rubble

Homestead Rubble is a unique blend of several styles of stone, including mosaics, ashlar, and ledgerstones. It can be installed with a mortar joint or in a dry-stacked style, but additional cutting and fitting may be required in a dry-stacked application.



 **Elkton Ridge**

Heights: 3" to 13"
Lengths: 7" to 24"



 **Rockland**

Heights: 2.5" to 10"
Lengths: 7" to 22"



 **Stony Point**

Heights: 3.5" to 12"
Lengths: 4" to 20"



Homestead Rubble Rockland

Ledgestone

Ledgestones vary greatly in appearance, but they are generally characterized as long narrow pieces. They can be installed with a mortar joint or in a dry-stacked style, but additional cutting and fitting may be required in a dry-stacked application.



 **Bar Harbor**

Heights: 2.5" to 8"
Lengths: 7" to 21"



 **Bayport**

Heights: 1.5" to 5"
Lengths: 5.5" to 21"



 **Charcoal Ridge**

Heights: 2" to 5"
Lengths: 4" to 24"



 **Cortland**

Heights: 2" to 6"
Lengths: 5" to 25"



 **Diamond Point**

Heights: 1" to 3"
Lengths: 6" to 16"



 **Grayhawk**

Heights: 1.5" to 7"
Lengths: 3" to 12"



 **High Point**

Heights: 1.25" to 5"
Lengths: 6" to 20"



 **Kingston**

Heights: 2" to 4"
Lengths: 6" to 14.5"



▲ **Locust Creek**

Heights: 3" to 5.5"
Lengths: 4" to 15"



▲ **Sheridan**

Heights: 3" to 7"
Lengths: 4" to 21"



■ **Silver Bay**

Heights: 2" to 6"
Lengths: 6" to 16"



▲ **Stony Point**

Heights: 1.5" to 5.5"
Lengths: 3.5" to 24"



■ **Woodbridge**

Heights: 1.25" to 6"
Lengths: 6" to 18"



Ledgestone Cortland

MetroFit

With clean lines and smooth texture, MetroFit adds an elegant and modern appeal to any space. All sides are sawn, and the face of each piece is lightly textured for a luxurious appearance. Each piece is 6" high, 30" wide, and 22mm thick, allowing for easy installation and a consistent appearance.



■ **Arctic Grey**

Size: 6" x 30"



■ **Yorkshire**

Size: 6" x 30"

PrecisionLedge

PrecisionLedge features pieces that are 2", 3" and 5" high, creating a clean and precise appearance. It is designed to be installed in a dry-stacked style, and the consistent piece heights allow for easy installation. The stones are cut on the top and bottom and snapped on the left and right edges.



 **Ashburn**

Heights: 2", 3", 5"
Lengths: 6" to 18"



 **Copper Canyon**

Heights: 2", 3", 5"
Lengths: 6" to 16"



 **Iron Mountain**

Heights: 2", 3", 5"
Lengths: 6" to 24"



 **Oxford**

Heights: 2", 3", 5"
Lengths: 6" to 20"



 **Plymouth**

Heights: 2", 3", 5"
Lengths: 4" to 20"



 **Potomac**

Heights: 2", 3", 5"
Lengths: 3" to 15"

Precision3

Precision3 pieces are cut to a uniform height of 3" and have varying lengths. All edges are sawn, creating a clean and modern appearance and simplifying installation. It is designed to be installed in a dry-stacked style.



 **Victoria**

Height: 3"
Lengths: 6" to 18"

QuarryField

QuarryField is designed to imitate stones often found near the surface layers of soil. It features a diverse selection of shapes and sizes with irregular edges, creating a natural appearance. It is typically installed with a mortar joint.



 **Charcoal Ridge**

Diagonal: 4" to 15"



 **Cortland**

Diagonal: 4" to 24"



 **Dakota Brown**

Diagonal: 7" to 14"



 **Holston Valley**

Diagonal: 4" to 19"



 **Locust Creek**

Diagonal: 2.5" to 19"



 **Mojave Buff**

Diagonal: 6" to 14"



 **Silver Bay**

Diagonal: 8" to 20"



 **Stony Point**

Diagonal: 8" to 19"

Rustic Ashlar

Rustic Ashlar features pieces that are mainly square or rectangular with a few angled or curved edges. The pieces tend to be larger and more square than Ledgerstone and are typically installed with a mortar joint.



 **Amarillo**
Featured on Front Cover

Heights: 2" to 12"
Lengths: 4" to 15"



 **Bayport**

Heights: 3.5" to 14"
Lengths: 5" to 16"



 **Charcoal Ridge**

Heights: 4" to 15"
Lengths: 4" to 15"



 **Copper Canyon**

Heights: 2" to 8"
Lengths: 6" to 16"



 **Dakota Brown**

Heights: 4" to 11"
Lengths: 6" to 18"



 **Elkton Ridge**

Heights: 4.5" to 16"
Lengths: 5" to 24"



 **Granite Falls**

Heights: 4" to 12"
Lengths: 6" to 20"



 **Grayhawk**

Heights: 2" to 10"
Lengths: 5.5" to 20.5"



▲ **Holston Valley**

Heights: 2" to 7"
Lengths: 5" to 17"



▲ **Maple Grove**

Heights: 2" to 10.5"
Lengths: 5.5" to 15"



▲ **Mojave Buff**

Heights: 4" to 10"
Lengths: 7" to 16"



■ **Silver Bay**

Heights: 2" to 8"
Lengths: 6" to 18"



▲ **Thunder Bay**

Heights: 2" to 10.5"
Lengths: 7" to 15"



▲ **Whitecliff**

Heights: 3" to 14"
Lengths: 7" to 17"



Rustic Ashlar Amarillo

SERIES DETAILS

■ **Foundation Series**

Focusing on a diverse yet affordable range of globally sourced products, these exceptionally beautiful products are the bedrock of Old World Stone Veneer.

▲ **Highlands Series**

Carefully sourced with exceptional quality, these stones are the best the eastern United States has to offer.

■ **Metro Series**

With a stylish urban feel, these stunning stones have modern, clean lines that are perfect for today's projects.

Accents

Our accents offer a beautiful appearance and the durability of natural stone. Headers, Sills, Hearthstones, Mantels, and Mantel Brackets are available.

Headers are typically used as accents above doors and windows. Sills are used under windows or at transitions. Hearthstones, Mantels, and Mantel Brackets are typically used on fireplaces.




Sable Headers




Yorkshire Headers

Header Size: 8" High, 22" Wide, 1" Thick
Sill Size: 2.5" Deep, 36" Wide, 2" Thick
Sills have 5 sawn edges and 1 rockfaced edge.




Autumn Brown Sills



Graphite Sills



Oceanside Sills




Sable Sills



Sedona Buff Sills



Summit Blue Sills



Yorkshire Sills



Summit Blue Mantel & Mantel Brackets

Mantel: 10" Deep, 60" Wide, 2" Thick, 4 Rockfaced Edges
Mantel Bracket: 7" Deep (Top), 2.5" Wide, 11" Tall, 5 Sawn Edges and 1 Rockfaced Edge



Summit Blue Hearthstone
 20" Wide, 20" Deep, 1.5" Thick
 4 Rockfaced Edges



Precision3 Victoria

Frequently Asked Questions (FAQ)

❓ What are the benefits of natural thin stone compared to manufactured stone?

Natural thin stone veneer offers many of the same benefits of manufactured stone veneer (lightweight, easy to install, no footer required) with the added benefit of being a natural product. Because natural stone products tend to be more durable than manufactured stone products, they will generally maintain their beauty much longer than manufactured stone. While all products exposed to sunlight will fade to varying degrees over time, natural stone tends to be more resistant to fading than manufactured stone. The depth and variation of color in natural stone are often much greater than its manufactured counterpart. Additionally, natural stone maintains its color throughout the piece, making it much more resilient against cutting, chipping, and breaking.

❓ Where is Old World Stone Veneer quarried?

Old World Stone Veneer is quarried from select locations around the world. If you would like more information about where a specific stone is quarried, please contact your local dealer.

❓ How should Old World Stone Veneer be installed?

Old World Stone Veneer is installed following the same basic procedures that are used for manufactured stone veneer. We recommend following the CMHA MSV guidelines for all preparatory steps; however, we strongly recommend the use of a modified thinset mortar to adhere natural stone thin veneer. These mortars adhere better to the smooth backs of sawn thin veneer than traditional Type S Mortar. Mortars should comply with the requirements of ANSI Standards A118.4 or A118.15. Visit www.oldworldstoneveneer.com for more information.

❓ What is the difference between a dry-stacked style application and a mortar joint/grouted application?

For either type of application, the surface preparation is the same (follow CMHA MSV guidelines), and the same mortar is used to adhere the stone to the wall. The difference between the two application styles only relates to the fitting of the stones and whether a mortar joint is used between the stones.

For a dry-stacked style application, pieces should generally be fitted together as tightly as possible with minimal gaps, which gives the pieces the appearance of being dry-stacked. Additional cutting and fitting may be required to achieve a tight fit. Mortar is used to adhere the stones to the wall, but no mortar joint is added between the stones after they are installed.

For a mortar joint/grouted application, the stones should be installed with a small space between each piece. The typical space is ¼" to ½", but a larger space can be used if a larger mortar joint is desired. After the stones are installed on the wall, mortar is added to the space between the stones (typically using a grout bag). The mortar joint is usually tooled and brushed to create a smooth, finished appearance.

❓ How much cutting and fitting is required during installation?

While every effort has been made to choose quality products that install with ease, cutting and fitting will be required during installation. All samples and photos required cutting and fitting to create the finished product. Some stone types may require more cutting and fitting than others. It is recommended that cutting and fitting be done with a wet or dustless saw to reduce dust and potentially harmful airborne contaminants that may be present in natural stone.

❓ Should natural stone veneer be sealed?

Many factors contribute to determining whether your job should be sealed. In most cases, it is not necessary to seal natural thin stone. Certain more porous stones do benefit from a coat of sealer in high exposure areas. If sealing is required or desired, the use of a breathable sealer is required. Before applying any sealer, the sealer manufacturer should be consulted to verify compatibility and applicability for your project.

❓ Are color variations and/or mineral deposits present in the stone?

Because Old World Stone Veneer is a product of nature, color variations should be expected. While every effort has been made to create photos, brochures, and samples that accurately depict the color range, due to limitations on printing and photographic technology, as well as a limited amount of space on sample boards, variations should be expected. Most stone types will have a larger color and size range than can be displayed in photos and samples. Additionally, changes within the quarries themselves can lead to variations over time as raw material changes in different areas in the quarries. Mineral deposits may be present in some stones and not others. These mineral deposits add to the beauty of the stone, but they can also lead to greater color variations, rust, or other discolorations over time. Old World Stone Veneer and its dealers cannot be responsible for natural variations or mineral deposits within the stone.

❓ How can natural stone be cleaned?

Old World Stone Veneer can be cleaned using a mild detergent and water with a stiff bristle brush. It can also be gently pressure washed; however, care must be taken to ensure that the surface of the stone is not damaged. Surrounding building fixtures should be protected when cleaning the stone surface. Acids, solvents, and harsh cleaners should not be used on natural stone products. Acids can react with the minerals in the stone and cause oxidation and discoloration. There are several cleaners that can be used to remove rust spots and oxidation. When cleaning, always test the cleaner on a small section before using it on your entire project.

❓ Can natural stone be used around salt water pools or areas frequently exposed to de-icing agents?

We recommend against using natural stone near areas where it will be directly exposed to salt. While not every stone reacts badly to salt, it can cause many undesirable effects. Additionally, salt can corrode the mortar which is used to install the stone. When de-icing areas near Old World Stone Veneer, it is important to make sure that the salt does not contact the stone directly.

❓ Does Old World Stone Veneer have a warranty?

Please see our statement of warranty for more information.

Important Note

Old World Stone Veneer products are grouped into general styles such as Rustic Ashlar or Ledgerstone for easy reference, but it is important to remember that products in the same style group may not have identical shape, size, and texture characteristics. Since products are naturally created, each individual stone type will have its own unique characteristics. Additionally, all sizes are approximate and may vary depending on availability of raw material. Visit our website to obtain specification sheets for each individual stone type.



Blend: 75% Castle Deep River, 25% Rustic Ashlar Thunder Bay

OLD WORLD STONE VENEER™

THE BEAUTY OF NATURE, PRESERVED IN STONE.

Visit our website for more product details,
high resolution photos, technical data, specification sheets,
installation guidelines, and other product resources.

www.oldworldstoneveneer.com

Old World Stone Veneer is natural stone. Since products are naturally created, variations in color and texture should be expected. The color and texture of products may vary from samples, displays, and photos. Colors in this brochure are as accurate as possible, but photographic and printing technologies, as well as actual viewing conditions, can alter the perception of color.