

ASHBURN PRECISIONLEDGE

Foundation Series



Photo Shows Dry-Stacked Installation

DESCRIPTION

Ashburn features a light color palette ranging from cream to light tan, with some spotters in a range of light red colors. PrecisionLedge features set heights at 2", 3", and 5" to allow for quicker installation and a sleek contemporary look. Each piece has sawn top and bottom edges with snapped ends, and many have a rough-textured face. It is traditionally installed in a dry-stacked style.

STONE TYPE

Limestone

WATER ABSORPTION

0.12%

SPECIFIC GRAVITY

2.72

DENSITY

169.8 lbs./cu. ft.

SIZE DETAILS

FLATS: SIZE RANGE

Height: 2", 3", 5"

Length: 6" to 18"

CORNERS: SIZE RANGE

Short Return: 4" to 8"

Long Return: 6" to 10"

TYPICAL THICKNESS

Thickness: 0.75" to 1.375"

PACKAGING DETAILS

CRATES

Flats: 100 Square Feet

Corners: 65 Lineal Feet

SMALL BOXES

Flats: 8 Square Feet

Corners: 6 Lineal Feet

All sizes are approximate and may vary depending on availability of raw material. Pieces are cut to a tolerance of 1/16" +/- . A small percentage of pieces may exceed this tolerance.