

PRECISIONLEDGE COPPER CANYON

Foundation Series



Photo Shows Dry-Stacked Installation

DESCRIPTION

PrecisionLedge Copper Canyon features a color range of light to medium browns with some dark browns intermixed. PrecisionLedge features set heights at 2", 3", and 5" to allow for quicker installation and a sleek contemporary look. Each piece has sawn top and bottom edges with snapped ends. It is traditionally installed in a dry-stacked style.

STONE TYPE

Sandstone

WATER ABSORPTION

0.95%

SPECIFIC GRAVITY

2.49

DENSITY

155.45 lbs./cu. ft.

SIZE DETAILS

FLATS: SIZE RANGE

Height: 2", 3", 5"

Length: 6" to 16"

CORNERS: SIZE RANGE

Short Return: 4" to 6"

Long Return: 6" to 10"

TYPICAL THICKNESS

Thickness: 0.75" to 1.5"

PACKAGING DETAILS

CRATES

Flats: 100 Square Feet

Corners: 65 Lineal Feet

SMALL BOXES

Flats: 8 Square Feet

Corners: 6 Lineal Feet

All sizes are approximate and may vary depending on availability of raw material. Pieces are cut to a tolerance of 1/16" +/-.

A small percentage of pieces may exceed this tolerance. A small percentage of Copper Canyon products have naturally occurring veins and fractures in the stones. These veins and fractures typically do not cause problems after installation, but they are weak points in the stones which may be susceptible to stress cracking under certain conditions.